

# ARTICRYL MAT

## DEFINITION

**ARTICRYL MAT** is a matt finish acrylic water based paint for usual works on interior walls and ceilings of dry premises, suitable for new or renovation works: parkings, garages, service premises, houses....

## PROPERTIES

- Very easy to apply and ready for use. recommended to be applied with spray gun.
- High matity and high spreading rate.
- Fast drying.
- High whiteness

## SUBSTRATES

suitable for interior new substrates (cement filler and by-products, cinder-block, concrete, cellular concrete, plaster and by-products, gypsum board, old adhering matt finish paint).

## TECHNICAL DATAS

### Classification

AFNOR NF T 36005 standard Family I-Class 7b2

### V.O.C.

E.U. limit value of this product (Cat. A/a) : 30 g/l (2010).

This product contains max. 10 g/l.

### Composition

Aqueous dispersion of acrylic polymers.

### Density

1.48 kg/l

### Non volatile matter

58.5 %

### Flash point

Not flammable

### Aspect

Matt

### Colour

White. Pastel colours obtained with 1% max. of solvent free universal dyestuffs.

### Drying at 20°C

Touch dry : 30 minutes - Recoatable : 3 to 4 hours

(Allow for adequate ventilation during the drying period).

### Spreading rate

8 to 10 sqm/l per coat according to substrate porosity and relief.

### Gloss to 60°

< 2

### Gloss to 85°

< 2

## USE ADVICES

### Substrates' preparation

On porous or powdery substrates or if applied with a brush or a roller, apply first a primer coat with **CELOPRIM** before painting.

### Application conditions

Apply **ARTICRYL MAT** with paint brush, synthetic short hairs roller or spay gun (nozzles from 0.015 to 0.017 inches. Remove oil, grease or any other contaminants and apply **ARTICRYL MAT** on a prepared, clean and dry substrate in accordance with NF P74-201-1 standard (DTU 59.1.). Do not apply when substrate temperatures are likely to fall below 8°C and above + 35°C or when the relative humidity is above 80% during application or the drying period.

Ready for use. Brew vigorously before application. Apply 2 coats of **ARTICRYL MAT**.

### Cleaning

Wash with water immediately after use.

### SHELF LIFE

2 years starting from the manufacturing date, in unopened packing of origin, stored in frost-free conditions.

### PACKAGING

15 L pails.

### HYGIENE AND SAFETY

SDS available on websites [www.artilin.fr](http://www.artilin.fr) or [www.quickfds.com](http://www.quickfds.com)

