

# CELOPRIM

<b>DEFINITION</b>	<b>CELOPRIM</b> is a multipurpose water based acrylic primer for interior and exterior walls and ceilings. Recommended to fix powdery substrates and to better the coverage of finishing coats.
<b>PROPERTIES</b>	<ul style="list-style-type: none"> <li>- Reduce the substrates defects</li> <li>- Excellent adherence</li> <li>- Water based formulation: comfort and safe when applied</li> <li>- low odour.</li> </ul>
<b>SUBSTRATES</b>	Cement filler and by-products, concrete, plaster and by-products, facing bricks, limestone, stones, old adhering matt finish paint.
<b>TECHNICAL DATAS</b>	
<b>Classification</b>	AFNOR NF T 36005 - Family I- Class 7b2
<b>V.O.C.</b>	E.C. limit value of this product (Cat. A/g):30 g/l (2010) . This product contains max. 30 g/l.
<b>Composition</b>	Aqueous dispersion of acrylic resins.
<b>Density</b>	1.4 kg/l
<b>Non volatile matter</b>	53%
<b>Flash point</b>	Not flammable
<b>Aspect</b>	Matt
<b>Colour</b>	White.
<b>Drying at 20°C</b>	Touch dry : 1 h. Recoatable:4 h. (values indicated for a well ventilated room).
<b>Spreading rate</b>	10 to 14 sqm/l per coat on smooth surface.
<b>Dilution</b>	Ready for use
<b>USE ADVICES</b>	
<b>Substrates preparation</b>	Dirt and non-adhering particles have to be eliminated with a high-pressure machine or by a scrubbing
<b>Application conditions</b>	<p><b>CELOPRIM</b> can be applied with a brush or a non spilling synthetic roller on a dry, clean and adhering substrate in accordance with the NFP 74-201-1 standard (D.T.U. 59.1). The substrate must be dry with superficial temperature of between +5°C and +35°C. Relative humidity during application: indoors max. 65% - outdoors max. is above 80% .</p> <p>Apply <b>CELOPRIM</b> as a primer coat.</p> <p><b>Important :</b> <i>CELOPRIM can be used as a primer before any ARTILIN's paint from the Specialities when a primer is recommended . Under paints resistant to mildew, it is compulsory to apply <b>GLYCEPRIM FONGE</b>.</i></p>
<b>Cleaning</b>	Wash with clean water immediately after use.
<b>SHELF LIFE</b>	2 years starting from the manufacturing date, in unopened packing of origin, stored in frost-free conditions.
<b>PACKAGING</b>	15 L pails
<b>HYGIENE AND SAFETY</b>	SDS available on websites <a href="http://www.artilin.fr">www.artilin.fr</a> or <a href="http://www.quickfds.com">www.quickfds.com</a> .



INTELLIGENT PAINT