

GLYCELO MAT FONGE

DEFINITION

GLYCELO MAT FONGE is a matt finish anti fungus water based paint with a very high coverage, based with alkyd resins in emulsion, specially developed to obtain an excellent finishing on interior walls and ceilings made with gypsum boards exposed to an environment favouring the development of mildew.
Two coats of **GLYCELO MAT FONGE** are enough to cover the base of gypsum boards, the coating over the joints and the fixing holes.

PROPERTIES

- Multipurpose paint.
- **Long lasting resistance against mildew (according to the AFNOR NF X41520 standard of resistance of paint to micro-organisms)**
- **Outstanding opacity: apply GLYCELO MAT FONGE directly on gypsum board without priming.**
Ready for use.
- Excellent filling and covering properties.
- Does not run or splash when applied.
- Recommended as first coat on glass textile wall covering and then apply **KREMASOIE FONGE** as satin/semi-gloss finishing coat.

SUBSTRATES

Gypsum boards on interior walls and ceilings
Other substrates : glass textile wall covering, wooden panels, extruded polystyrene, cement coating, brick, cinder block, old adhering matt finish paints, plaster and plaster by-products, cellular concrete, timber.

TECHNICAL DATAS

Classification V.O.C.

AFNOR NFT 36005 – Family I – Class 7a2
E.U. limit value of this product : (cat A/a) : 30 g/l (2010).
This product contains max.15 g/l.

Composition

Mixed vinyl-alkyd aqueous dispersion. Contains a film preservative agent.

Density

1.55 kg/l

Non volatile matter

66%

Flash point

Not flammable

Aspect

Matt

Colour

White. Pastel colours obtains with 1% max. of solvent free universal dyestuffs.

Drying at 20°C

Dust proof : 1 hour - Recoatable : 6 hours (*allow for adequate ventilation during the drying period*).

Spreading rate

8 to 11 sqm/l per coat according to substrate porosity and relief (i.e. 140 to 200 g/sqm
Respect this quantity : higher quantities applied with the airless spray would cause some aspect defects.

Gloss at 60°

1 to 2

Gloss at 85°

About 1

USE ADVICES

Substrates' preparation

In case of substrates covered over with mildew, before painting, it is necessary to eliminate all the organic growth with a humid scrubbing (sponge or scrubbing-brush) or high-pressure machine. Then disinfect the substrate with **ARTIBIOSE+** solution.

Application conditions

GLYCELO MAT FONGE can be applied with a brush, a roller or a pulverizer on a prepared clean and dry substrate according to the NF P 74-201-1 standard (D.T.U 59.1). Do not apply when substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application.

In the case of application on old bases, on wood or with airless spray gun, dilute with water if necessary (3% maximum).

On old bases still powdery after preparation, apply **GLYCEPRIM FONGE** to fix the base.

On plaster and plaster blocks thin the first coat of **GLYCELO MAT FONGE** with 5% to 10% clean water.

Apply 2 coats of **GLYCELO MAT FONGE** to obtain a total opacity.

Important : **GLYCELO MAT FONGE** must be neither covered nor mixed with any other paint in order to keep its moulds resistance.

Cleaning

Wash with clean water immediately after use.

SHELF LIFE

2 years from the manufacturing date, in unopened packing of origin, stored in frost-free conditions.

PACKAGING

15 L pails.

HYGIENE AND SAFETY

SDS available on websites www.artilin.fr or quickfds.com



INTELLIGENT PAINT

B.P. 12 - 47450 COLAYRAC-SAINT-CIRQ - FRANCE
Tél : +33(0)5.53.87.16.40. - Fax : +33(0)5.53.87.16.42
E-mail : artilin@artilin.fr

REMARK :
As we do not know in which conditions our products are used, our responsibility cannot be engaged when the instructions here above indicated are not respected, being based upon test results carried out in our laboratories.