

# KREMABRILL FONGE

## DEFINITION

**KREMABRILL FONGE** is a glossy paint, water based, anti fungus for interior and exterior walls and ceilings.  
This paint is a real alternative to traditional solvent based gloss paint.  
**Recommended in bathrooms, kitchens, stairwells, eaves, wood-works...**

## PROPERTIES

- **Long lasting resistance to mildew (according to the NF X41520 standard of paints resistance to micro organisms).**
- Resistance to humid frictions according to EN ISO 11998 and NF EN 13300 : washable Class 1. (abrasion < 5 µm)
- **Water based** : very low odour, comfort and safety of use.
- Excellent resistance to yellowing
- Rapid drying.

## SUBSTRATES

Old matt finish adherent paint. Other substrates : see § substrates' preparations.

## TECHNICAL DATAS

### Classification V.O.C.

AFNOR NFT 36005 – Family I – Class 7b2  
E.U. limit value of this product : (cat A/b) : 100 g/L (2010).  
This product contains max.100 g/l.

### Composition

Acrylic polymeric emulsion. Contains a film preservative agent.

### Density

1.24 kg/l

### Non volatile matter

50%

### Flash point

Not flammable

### Aspect

Tight gloss

### Colour

White. Pastel colours obtained with 2% maximum of solvent free dyestuffs.

### Drying at 20°C

Touch dry : 1 hour - Recoatable: 6 hours (values given as a rough guide).

### Spreading rate

10 to 12 sqm/l per coat according to substrate nature.

### Gloss at 60°

75

### Dilution

Ready for use.

## USE ADVICES

### Substrates' preparation

On semi-gloss or gloss old bases it is necessary to rub down.  
Dirt and non adherent particles must be removed as much as possible by scrubbing.  
In case of substrates covered over with mildew, before painting, it is necessary to eliminate all the organic growth with a humid scrubbing or high-pressure machine. Then disinfect the substrate with **ARTIBIOSE+** solution.  
On gypsum board, apply **GLYCELO MAT FONGE** as first coat. On all other interior non-painted bases prime with **GLYCEPRIM FONGE**.  
On exterior non-painted bases, prime with **GLYCELITE FAÇADE FONGE** thinned with 20% of clean water.

### Application conditions

**KREMABRILL FONGE** can be applied with a brush or a roller special for acrylic glossy paint on an adherent, prepared clean and dry substrate according to the NF P 74-201-1 standard (D.T.U 59.1).  
Temperature for application : between 8°C and 30°C. Maximum hygrometry : 65% relative humidity.  
It is necessary to apply 2 coats of **KREMABRILL FONGE** to obtain the best resistance against mildew.

**Important : KREMABRILL FONGE must be neither covered nor mixed with any other paint in order to keep its properties of resistance against mildew.**

### Cleaning

Wash with clean water immediately after use.

### SHELF LIFE

2 years from the manufacturing date, in unopened packing of origin, stored in frost-free conditions.

### PACKAGING

15 L pails

### HYGIENE AND SAFETY

SDS available on websites [www.artilin.fr](http://www.artilin.fr) or [quickfds.com](http://quickfds.com)

