

KREMASOIE FONGE A

DEFINITION

KREMASOIE FONGE A is a semi-gloss finish water based anti fungus paint for interior walls and ceilings.

Use **KREMASOIE FONGE A** as finishing coat on glass textile wall covering.

KREMASOIE FONGE A is recommended in food industry locals, cold rooms, slaughterhouses, staff canteen as well as in hospitals ...

PROPERTIES

-
- Thanks to its exceptional resistance to mildew (according to the AFNOR NFX 41520 standard), **KREMASOIE FONGE A** assures the long-lasting protection of walls and ceilings, which are subject to the proliferation of moulds.
- Resists to the mucor non-standard fungus (ITECH Laboratory in Lyon)
- Washable (test report according to NF T30082 standard)
- IANESCO test report allowing the occasional food contact in cold rooms. Concern only white paint (not dyed).
- **KREMASOIE FONGE A** owns the Green Label from Excell® Laboratory : does not contain any chlorophenol, chlorobenzene or organochlorinated components, that can deteriorate the taste of wine or the taste of food during an application in wine storehouses or in stock and transformation areas in food industry locals.
- **Not yellowing**
- Resistant to humid abrasion (EN ISO 11998 and NF EN 13300 : washable class 1 (abrasion < 5 µm)).

SUBSTRATES

Cement, brick, cinder-block, interior rendering, old matt finish adhering paint, glass textile wall covering, timber and timber by-products, plaster and plaster by-products.

TECHNICAL DATAS

Classification V.O.C.

AFNOR NF T 36005 family I - class 7b2
E.U. limit value of this product : (cat A/b) :100 g/l (2010).
This product contains max. 95 g/l.

Composition

Aqueous dispersion of acrylic copolymers. Contains a film preservative agent.

Finish

Tight semi-gloss

Density

1.4 kg/l

Non volatile matter

55%

Flash point

Not flammable

Colour

White. Pastel colours obtained with 1% maximum of solvent free dyestuffs.

Drying time at 20°C

Dust proof : 2 hours - Recoatable : 8 hours (*Allow for adequate ventilation during the drying period*).

Spreading rate

9 to 12 sqm/l per coat according to substrate porosity and relief.

Gloss at 60°

35

USE ADVICES

Surface preparation

Rub down the old substrates already painted with semi-gloss or gloss finish paint before painting.
In case of substrates covered over by mildew, it is necessary to remove all the organic growth (with brush, high pressure machine...) and then disinfect with **ARTIBIOSE+** solution.
On old substrates still powdery after preparation, fix with **GLYCEPRIM FONGE**.
On non-painted surfaces, prime with **GLYCEPRIM FONGE**.

Application

Apply **KREMASOIE FONGE A** with a brush, a roller or a spray gun on adherent, free of dust, clean and dry substrate in accordance with NF P74-201-1 standard (DTU 59.1.).
Do not apply when air or substrate temperature are likely to fall below 8°C or when the ambient air is saturated with humidity.
Thin with clean water if necessary (3% maximum).
To obtain a better efficacy apply 2 coats of **KREMASOIE FONGE A**.

Important : KREMASOIE FONGE A must not be covered over or mixed with any other paint to keep its properties of resistance to mildew.

Cleaning

Wash with clean water immediately after use.

SHELF LIFE

2 years starting from the manufacturing date, in unopened packing of origin, stored in frost-free conditions.

PACKAGING

15 L pails and cardboard boxes of 4 x 2.5 L each.

HEALTH AND SAFETY

SDS available on websites www.artilin.fr or quickfds.com

