

# KREMASOIE FONGE

## DEFINITION

**KREMASOIE FONGE** is a satin/semi-gloss finish acrylic water based anti fungus paint for interior and exterior walls and ceilings.

Use **KREMASOIE FONGE** as finishing coat on glass textile wall covering.

**Recommended for all interior decoration works: corridors, bedrooms, bathrooms in private or collective premises like hospitals, retirement homes, health establishments, hotels, schools...**

## PROPERTIES

- Ready for use.
- **Long lasting resistance against mildew (according to the AFNOR NF X 41520 standard).**
- Excellent resistance to yellowing.
- **Washable (NF T30082 standard).**
- Resistant to humid abrasion (EN ISO 11998 and NF EN 13300) : washable class 1 (abrasion < 5 µm)

## SUBSTRATES

Cement and cement by-products, brick, cinder-block, rendering, interior renders, old matt adhering paint, glass textile wall covering, timber and timber by-products, plaster and plaster by-products.

## TECHNICAL DATAS

### Classification V.O.C.

AFNOR NF T36005 standard Family I-Class 7b2

E.U. limit value of this product : (cat A/b) : 100 g/l (2010).

This product contains max. 100 g/l.

### Composition

Aqueous dispersion of acrylic copolymers. Contains a film preservative agent.

### Density

1.4 kg/l

### Non volatile matter

55%

### Flash point

Not flammable

### Aspect

Tight semi-gloss

### Colour

White. Pastel to medium colours obtained with 5% max. of solvent free universal colours.

### Drying at 20°C

Dust proof : 2 hours - Recoatable : 8 hours (*Allow for adequate ventilation during the drying period*).

### Spreading rate

9 to 12 sqm/l per coat according to substrate porosity and relief.

### Gloss at 60°

35

## USE ADVICES

### Substrates' preparation

On semi-gloss or gloss old bases, rub down obligatory before painting. In case of substrates covered over with mildew, before painting, it is necessary to eliminate all the organic growth with a humid scrubbing (sponge or scrubbing-brush) or high-pressure machine. Then disinfect the substrate with **ARTIBIOSE+** solution.

On old bases still powdery after preparation, prime with **GLYCEPRIM FONGE** to fix the base.

On non-painted substrates, prime with **GLYCEPRIM FONGE** before painting.

### Application conditions

Apply **KREMASOIE FONGE** with paint brush, conventional roller or spay gun on a prepared, clean and dry substrate in accordance with NF P74-201-1 standard (DTU 59.1.). Do not apply when substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period. Dilute with clean water if necessary (3% maximum).

Apply two coats of **KREMASOIE FONGE** to obtain a maximum resistance against mildew.

**Important : KREMASOIE FONGE must be neither covered nor mixed with any other paint in order to keep its moulds resistance.**

### Cleaning

Wash with clean water immediately after use.

### SHELF LIFE

2 years from the manufacturing date, in unopened packing of origin, stored in frost-free conditions.

### PACKAGING

15 L pails and cardboard boxes of 4 x 2.5 L

## HYGIENE AND SAFETY

SDS available on websites [www.artilin.fr](http://www.artilin.fr) or [quickfds.com](http://quickfds.com)



INTELLIGENT PAINT