

KREMABIOSE

DEFINITION

KREMABIOSE is a matt finish vinyl-alkyd moulds resistance water based paint for interior and exterior walls and ceilings.

Recommended for all mouldy or tending to be mouldy substrates.

PROPERTIES

- Ready for use.
- **Long lasting resistance against moulds (according to the AFNOR NF X 41520 standard).**
- Excellent adherence to all old or new masonry materials.

SUBSTRATES

Cement and cement by-products, cellular concrete brick, cinder-block, plaster and plaster by-products, old matt finish adhering paint, timber and timber by-products.

TECHNICAL DATAS

Classification

AFNOR NFT 36005 – Family I – Class 7a2

V.O.C.

E.U. limit value of this product : (cat A/a) : 75 g/l (2007) / 30 g/l (2010).

This product contains max. 15 g/l.

Composition

Mixed vinyl-alkyd aqueous dispersion. Contains a film preservative agent.

Density

1.55 kg/l

Non volatile matter

66%

Flash point

Not flammable.

Aspect

Matt

Colour

White. Pastel colours obtains with 2% max. of solvent free universal dyestuffs.

Drying at 20°C

Dust proof : 1 hour - Recoatable : 6 hours (*allow for adequate ventilation during the drying period*).

Spreading rate

5 to 7 sqm/kg (7 to 10 sqm/l) per coat according to substrate porosity and relief.

Gloss at 60°

1 to 2

USE ADVICES

Substrates' preparation

In case of substrates covered over with moulds, before painting, it is necessary to eliminate all the moulds with a humid scrubbing (sponge or scrubbing-brush) or high-pressure machine. Then disinfect the substrate with **ARTIBIOSE+** solution.

In case of still powdery substrates after preparation, fix with **GLYCEPRIM FONGICIDE**.

Application conditions

KREMABIOSE can be applied with a brush, a roller or a pulverizer on a prepared clean and dry substrate according to the NF P 74-201-1 standard (D.T.U 59.1). Do not apply when substrate temperatures are likely to fall below 8°C or higher than 35°C or when the relative humidity is above 80% during application. Ventilate well during application.

In the case of application on old bases, on timber or with airless spray gun, thin with clean water if necessary (3% maximum). On plaster and plaster blocks thin the first coat of **KREMABIOSE** with 5% clean water.

Apply two coats of **KREMABIOSE** to obtain a maximum moulds resistance.

Important : KREMABIOSE must be neither covered nor mixed with any other paint in order to keep its moulds resistance.

Cleaning

Wash with clean water immediately after use.

STORAGE

2 years from the manufacturing date, in unopened packing of origin, stored in frost-free conditions. Limit date of use and batch n° : see white label on the body of the tin.

PACKAGING

15 L tins and cardboard boxes of 4 tins of 2.5 L each.

HYGIENE AND SAFETY

SDS available on websites www.artilin.fr or quickfds.com



INTELLIGENT PAINT

B.P. 12 - 47450 COLAYRAC-SAINT-CIRQ - FRANCE
Tél : +33(0)5.53.87.16.40. - Fax : +33(0)5.53.87.16.42
E-mail : artilin@artilin.fr

REMARK :
As we do not know in which conditions our products are used, our responsibility cannot be engaged when the instructions here above indicated are not respected, being based upon test results carried out in our laboratories.