

KREMASOIE



DEFINITION

KREMASOIE is a semi-gloss finish acrylic water based paint for interior and exterior walls and ceilings.

Use **KREMASOIE** as finishing coat on glass textile wall covering.

Recommended for all interior decoration works: corridors, bedrooms, bathrooms in private or collective premises like hospitals, retirement homes, hotels, schools...

PROPERTIES

- Ready for use.
- Excellent resistance to yellowing.
- Green Label EXCELL®

SUBSTRATES

Cement and cement by-products, brick, cinder-block, rendering, interior renders, old matt adhering paint, glass textile wall covering, timber and timber by-products, plaster and plaster by-products.

TECHNICAL DATAS

Classification V.O.C.

AFNOR NF T 36005 standard Family I-Class 7b2

E.U. limit value of this product (Cat. A/b) : 150 g/l (2007) / 100 g/l (2010).

This product contains max. 100 g/l.

Composition

Aqueous dispersion of acrylic copolymers.

Density

1.4 kg/l

Non volatile matter

56 %

Flash point

Not flammable

Aspect

Tight semi-gloss

Colour

White. Pastel colours obtained with 2% max. of solvent free universal dyestuffs.

Drying at 20°C

Touch dry : 2 hours - Recoatable : 8 hours (*Allow for adequate ventilation during the drying period*).

Spreading rate

9 to 12 sqm/l per coat according to substrate porosity and relief.

Gloss to 60°

30

USE ADVICES

Substrates' preparation

On semi-gloss or gloss old bases, rub down obligatory before painting. On old bases still powdery after preparation, apply **GLYCEPRIM FONGICIDE** to fix the base.

On non-painted substrates, apply first a primer coat with **GLYCEPRIM FONGICIDE** before painting.

Application conditions

Apply **KREMASOIE** with paint brush, conventional roller or spay gun. Remove oil, grease or any other contaminants and apply **KREMASOIE** on a prepared, clean and dry substrate in accordance with NF P74-201-1 standard (DTU 59.1.).

Do not apply when substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period. Ready for use. Dilute with water if necessary (3% maximum).

On glass textile wall covering before applying **KREMASOIE** as finishing coat, apply first **GLYCELO MAT**.

Cleaning

Wash with water immediately after use.

STORAGE

Store in frost-free conditions.

PACKAGING

15 L tins.

HYGIENE AND SAFETY

SDS available on websites www.artilin.fr or www.quickfds.com

REMARK :

As we do not know in which conditions our products are used, our responsibility cannot be engaged when the instructions here above indicated are not respected, being based upon test results carried out in our laboratories.



B.P. 12 - 47450 COLAYRAC-SAINT-CIRQ - FRANCE
Tél : +33(0)5.53.87.51.65. - Fax : +33(0)5.53.676.676
E-mail : artilin@artilin.fr