

# VINYMAT

## DEFINITION

**VINYMAT** is a matt finish water based paint for interior walls and ceilings.

Recommended for all usual new decoration works or in renovation.

## PROPERTIES

- Good dry and humid opacity. Low V.O.C. rate.
- High matity and spreading rate.
- Fast drying and high whiteness.
- Good filling properties, easy to apply.

## SUBSTRATES

Cement and by-products, cellular concrete, plaster and by-products, wood and by-products, old adhering matt paint.

## TECHNICAL DATAS

### Classification

AFNOR NF T 36005 standard Family I-Class 7a2

### V.O.C.

E.U. limit value of this product (Cat. A/a) : 30 g/l (2010).

This product contains max. 20 g/l.

### Composition

Aqueous vinylic dispersion.

### Density

1.4 kg/l

### Non volatile matter

55 %

### Flash point

Not flammable

### Aspect

Matt

### Colour

White. Pastel colours obtained with 5% max. of solvent free universal dyestuffs.

### Drying at 20°C

Touch dry : 1 hour - Recoatable : 6 hours

(Allow for adequate ventilation during the drying period).

### Spreading rate

11 to 14 sqm/l per coat according to substrate porosity and relief.

### Gloss to 60°

< 2

### Gloss to 85°

< 2

## USE ADVICES

### Substrates' preparation

On porous or powdery substrates, apply first a primer coat with **CELOPRIM** before painting

### Application conditions

Apply **VINYMAT** with paint brush, synthetic short hair roller or spay gun (nozzles from 0.015 to 0.017 inches. Remove oil, grease or any other contaminants and apply **VINYMAT** on a prepared, clean and drysubstrate in accordance with NF P74-201-1 standard (DTU 59.1.). The substrate must be dry with superficial temperature of between +5°C and +35°C. Do not apply when the relative humidity is above 80% during application or the drying period. Ready for use. Apply 1 or 2 coats of **VINYMAT** according to the level of finishing required.

### Cleaning

Wash with clean water immediately after use.

### SHELF LIFE

2 years starting from the manufacturing date, in unopened packing of origin, stored in frost-free conditions.

### PACKAGING

15 L pails.

### HYGIENE AND SAFETY

SDS available on websites [www.artilin.fr](http://www.artilin.fr) or [www.quickfds.com](http://www.quickfds.com)



INTELLIGENT PAINT

B.P. 12 - 47450 COLAYRAC-SAINT-CIRQ - FRANCE  
Tél : +33(0)5.53.87.16.40. - Fax : +33(0)5.53.87.16.42  
E-mail : [artilin@artilin.fr](mailto:artilin@artilin.fr)

REMARK :  
As we do not know in which conditions our products are used, our responsibility cannot be engaged when the instructions here above indicated are not respected, being based upon test results carried out in our laboratories.