

VINYSOIE

DEFINITION

VINYSOIE is a soft semi-gloss finish vinylic water based paint for interior new usual works on walls and ceilings or in renovation.

PROPERTIES

- Very easy to apply.
- Good opacity and high spreading rate.
- Low V.O.C. rate.
- Good filling properties

SUBSTRATES

On new interior substrates with application of a primer coat (cement and by-products, brick, cinder-block, interior renders, plaster and by-products, gypsum boards, wood and by-products) and on old adhering matt paint, glass textile wall covering.

TECHNICAL DATAS

Classification

AFNOR NF T 36005 standard Family I-Class 7a2

V.O.C.

E.U. limit value of this product (Cat. A/a) : 30 g/l (2010).

This product contains max. 15 g/l.

Composition

Vinylic aqueous dispersion.

Density

1.3 kg/l

Non volatile matter

58 %

Flash point

Not flammable

Aspect

Soft semi-gloss

Colour

White. Pastel colours obtained with 5% max. of solvent free universal dyestuffs.

Drying at 20°C

Touch dry : 1 to 2 hours - Recoatable : 8 hours

(Allow for adequate ventilation during the drying period).

Spreading rate

11 to 14 sqm/l per coat according to substrate porosity and relief.

Gloss to 60°

18

USE ADVICES

Substrates' preparation

On non-painted cement or plaster substrates and on gypsum boards, apply first a primer coat with **CELOPRIM** before painting. On wooden substrates, apply first a primer coat with **GLYCEPRIM FONGE**.

Application conditions

Apply **VINYSOIE** with paint brush, conventional roller or spay gun (nozzles from 0.015 to 0.017 inches). Remove oil, grease or any other contaminants and apply **VINYSOIE** on a prepared, clean and dry substrate in accordance with NF P74-201-1 standard (DTU 59.1.). Do not apply when substrate temperatures below 8°C or up to 35°C or when the relative humidity is above 80% during application or the drying period. Ready for use. Apply 1 or 2 coats of **VINYSOIE** according level of finishing required.

Cleaning

Wash with clean water immediately after use.

SHELF LIFE

2 years starting from the manufacturing date, in unopened packing of origin, stored in frost-free conditions.

PACKAGING

15 L pails.

HYGIENE AND SAFETY

SDS available on websites www.artilin.fr or www.quickfds.com

