

VINYVELOURS

DEFINITION

VINYVELOURS is a semi-gloss finish vinylic water based paint for usual interior works on walls and ceilings.

PROPERTIES

- Very easy to apply.
- Good opacity and high spreading rate.
- Fast drying.
- High whiteness.

SUBSTRATES

In the case of new substrates apply a primer before applying VINYVELOURS (cement and by-products, gypsum boards, plaster and by-products, old adhering matt paint, glass textile wall covering).

TECHNICAL DATAS

Classification

AFNOR NF T 36005 standard Family I-Class 7a2

V.O.C.

E.U. limit value of this product (Cat. A/a) : 30 g/l (2010).

This product contains max. 15 g/l.

Composition

Vinylic aqueous dispersion.

Density

1.25 kg/l

Non volatile matter

46 %

Flash point

Not flammable

Aspect

Soft semi-gloss

Colour

White. Pastel colours obtained with 1% max. of solvent free universal dyestuffs.

Drying at 20°C

Touch dry : 30 minutes - Recoatable : 4 to 6 hours

(Allow for adequate ventilation during the drying period).

Spreading rate

12 to 16 sqm/l per coat according to substrate porosity and relief.

Gloss to 60°

12

USE ADVICES

Substrates' preparation

On non-painted cement or plaster substrates, apply first a primer coat with **CELOPRIM** before painting. On gypsum boards and glass textile wall coverings, apply first a primer coat with **GLYCELO PREMIUM** or **GLYCELO MAT**.

Application conditions

Apply **VINYVELOURS** with paint brush, conventional roller or spay gun (nozzles from 0.015 to 0.017 inches). Remove oil, grease or any other contaminants and apply **VINYVELOURS** on a prepared, clean and dry substrate in accordance with NF P74-201-1 standard (DTU 59.1.). The substrate must be dry with superficial temperature of between +5°C and 35°C. Do not paint when the relative humidity is above 80% during application or the drying period. Ready for use. Do not dilute. Brew vigorously before application.

Apply 2 coats of **VINYVELOURS**.

Cleaning

Wash with clean water immediately after use.

SHELF LIFE

2 years starting from the manufacturing date, in unopened packing of origin, stored in frost free conditions.

PACKAGING

15 L pails.

HYGIENE AND SAFETY

SDS available on websites www.artilin.fr or www.quickfds.com

